

## ADVANTAGES

- Excellent material for filling deep ruts, cracks, and holes in concrete floors.
- Skid and slip-resistant surface is easy to clean. Approved by U.S.D.A. for use in meat packing plants.
- Mixes easily — Applies easily. No objectionable odor.
- Cures quickly.
- Adheres to practically every substrate and surface, including concrete, metal, wood, ceramics, marble, terrazzo, etc.
- Excellent for use in: Dairies, Bottling Plants, Food Plants, Chemical Plants, Swimming Pools, Bridges, Sugar & Oil Refineries, Kitchens, Laundries, Piers/Docks, and Tunnels.

# INDUSTRIAL SURE - BOND

## MIXING DIRECTIONS

Thoroughly mix the liquid in the container and slowly add 3 to 5 parts aggregates. Stir constantly until all the materials are completely blended to the same consistency as a plastic concrete mixture. Mix only when ready to use.

## APPLICATION

Place mixture to the desired depth using a screed, float, or trowel, until a level, smooth surface is attained. Surface texture may be trowelled smooth or coarse in the same manner as concrete.

USE WITH ADEQUATE VENTILATION  
store in a cool dark place.

DO NOT INGEST. AVOID PROLONGED CONTACT WITH SKIN  
AND EYES. AFTER FINISHING JOB WASH HANDS THOR-  
OUGHLY WITH POWDERED OR GRIT SOAP. USE PROTECTIVE  
GOGGLES AND GLOVES.

- PATCHING
- RESURFACING
- WATERPROOFING
- BONDING
- CHEMICAL RESISTANT
- SLIPPROOFING

**U.S.D.A. Approved**  
HEAVY DUTY, RESISTS ACIDS, CHEMICALS  
and SOLVENTS  
WITHSTANDS "HEAVY" TRAFFIC